DOERK·HOLZ

NATÜRLICH. NACHHALTIG.

Verpackungs- und Bausperrholz

Stärke [mm]	Wisa Spruce Qual. 2/3 GESCHL.,EN 636-2 S Format [mm] 2500 x 1250	Seekiefer Qual. 3/3 EN 636-3 S Format [mm] 2500 x 1250	Bras. Elliottis-Pine C+/C WBP verleimt Format [mm] 2440 x 1220	Industriesperrholz, rot, BB/CC Mittellage Eukal./Pappel, exterior, E1 Format [mm] 2440 x 1220
4				N
5				N
6				N
8				N
9	ZL	N	ZL	
12	N	N	ZL	N
15	N	N	ZL	N
18	N	N	ZL	N
20			ZL	N
21	N	N		
24	N			
25		N		N
30	ZL	N		
40	ZL			

Beton/ Fahrzeugbau

Stärke [mm]	Betonschalungsplatten Birke , EN636-2s		Siebdruckplatten Birke , EN636-2s			Siebdruckplatten Maxi Birke , EN636-2s	
	Format [mm]						
	1250 x 2500	1500 x 3000	1250 x 2500	1500 x 2500	1500 x 3000	2000 x 3000	2150 x 4000
6,5	N	ZL	ZL		ZL		
9	N	ZL	ZL	N	ZL		
12	N	ZL	ZL	N	ZL		ZL
15	N	ZL	N	N	N	ZL	ZL
18	N	ZL	N	N	N	ZL	N
21	N	ZL	N	N	N	ZL	N
24	ZL		ZL	N	ZL		ZL
27			ZL	N	ZL		
30			ZL	N	ZL		
35				ZL			
40		ZL			ZL		

08.2023

N = ab Lager Neckarsulm ZL = Zentral-Lager mit 3-4 Tagen Lieferzeit

Eduard Doerk GmbH & Co. KG | Holzhandel - Holzimport | Rötelstraße 40 | 74172 Neckarsulm
www.doerk.de | info@doerk.de | 07132 - 326-0